




Type TL08X-18YP-AN6-C2
Ident No. 12802011

- Threaded barrel, M18x1
- Chrome-plated brass
- 3-wire, 10...30VDC
- cable

技术参数

Technical parameter

电气参数 electrical parameter

Rated switching distance S_n	8 mm
Assured switching distance S_r	$\leq (0.81 \times S_n)$ mm
Mounting conditions	Non-flush
Operating voltage	10...30 VDC
Pulsating voltage	$\leq 20\%$
DC rated operational current	≤ 100 mA
No-load current	≤ 10 mA
Voltage drop at I_e	≤ 2 V
Repeatability	$\leq 5\%$ S_r
Hysteresis	3...15% S_r
Temperature drift	$\leq \pm 10\%$
Switching frequency	500 Hz
Output function	3-wire NPN , NO
Short-circuit protection	yes
Reverse polarity protection	yes
Switching state	LED , yellow
Vibration resistance	55Hz (1mm)
Shock resistance	30g (11ms)
IP rating	IP67
Certification	CE

机械参数 mechanical parameter

Dimension	M18x1
Housing material	metal, CuZn-Cr
Material active area	PBT
End cap	PA
Max.tightening torque housing nut	25Nm
Connection	cable
Cable quality	PVC , 2m
Cable cross section	3 x 0.34 mm ²
Ambient temperature	-25...70°C

接线图

Wiring diagram

